
HIGH PERFORMANCE CONCRETE WITH EXTENDED JOINTS

752HP FLOOR SYSTEM









TYPICAL APPLICATIONS

- Warehouses
- Distribution Centers
- Manufacturing Plants
- Commercial and Retail Floors
- Recreational Facilities
- Food and Beverage Processing

FEATURES & BENEFITS

- Reduction of contraction joints
- More durable concrete
- Less maintenance
- Reduced construction time
- Lower cost of installation
- Specification direction
- On-site field support

GUIDES & STANDARDS

- ACI 302
- ACI 360
- ASTM C78 and C1609
- ASTM C157 modified

A PROPOSAL FOR ADVANCED FLOOR DESIGNS

Euclid Chemical 752HP Floor System is a high flexural strength, low shrinkage, high performance, fibre-reinforced concrete floor designed to extend joint spacing, reduce curling and improve lifetime serviceability. This system is intended for interior industrial and commercial floors built in accordance with ACI 302 and 360.

THE OBJECTIVE AND THE GOAL

Euclid Chemical 752HP Floor System comprises the following components:

- 5.2 MPa flexural strength concrete mixture
- 0.02% concrete shrinkage
- 1.4 MPa post-crack residual strength (f_{e3})
- 15 m joint spacing (column line spacing)

PRODUCTS

The Euclid Chemical Company offers the following products to assist in the development and successful placement of the Euclid Chemical 752HP Floor System:

- CONEX shrinkage compensating admixtures
- TUF-STRAND SF macro-synthetic fibres
- EUCO QWIKJOINT UVR joint fillers
- EUCO DIAMOND HARD surface densifier
- EUCON (or similar) high performance water-reducers and chemical admixtures
- PLASTOL (or similar) series of polycarboxylate chemical admixtures

EXPERTISE, SERVICE AND EXPECTATIONS

By utilising the products, technical data, specifications, contractor relationships, and laboratories at Euclid Chemical, a successful low shrinkage, high performance, extended joint, fibre-reinforced concrete floor can be built that will provide the owner with lower maintenance and better durability over the expected lifetime.

GETTING STARTED

With advancements in concrete placement, reinforcing technologies, admixture capabilities and repair methods, concrete floor construction has evolved beyond traditional placement techniques. The **Euclid Chemical 752HP Floor System** and specification combines emerging technologies and provides guidance for topics such as extended joint spacing, low shrinkage, fibre-reinforcement, curing methods, decorative applications and troubleshooting problems.



SPECIFICATIONS & RECOMMENDATIONS	
Subgrade	0.041N/mm³ at time of concrete placement
Curing	7 day wet
Isolation Joints	Follow ACI guidelines
Saw Cutting	Minimum D/3: if necessary, immediate early entry, follow up at 4-6 hrs
Slip Sheets	0.38 mm min. single sheet with taped overlaps
Joint Filling	> 120 days

Conventional Floor Joints @ 3.8 m Joints @ 15 m

Reduction in lineal feet of joint up to 80%

ALTERNATIVES

The potential for extending joint spacing can depend on more than just the mix design and reinforcement. Proper subgrade preparation, placement conditions, saw cut depth, curing time, and exposure can all play a role in the overall floor lifetime serviceability. Alternative flexural strengths, fibre dosages, joint spacing, and chemical admixtures can all be used to construct durable high performance floors. It is highly recommended to conduct testing and verification prior to the construction of a floor project to ensure engineering and specification requirements are met.







For more than 100 years, The Euclid Chemical Company has served as a leading supplier to the concrete and masonry industry offering a full line of engineered concrete admixture and construction products marketed under the EUCO brand name. These products include concrete admixtures, block and masonry additives, curing and sealing compounds, epoxy adhesives, floor and wall coatings, structural grouts for columns, equipment and machinery, joint fillers and repair products. Euclid Chemical products are supplied by Tremco Construction Products Group in Asia Pacific. Visit www.tremcocpg-asiapacific.com for more information.



APAC140722