

COLOR RELEASE

COLOURED STAMP TOOL RELEASING POWDER

DESCRIPTION

COLOR RELEASE is a ready to use, dry-shake releaser available in variety of colours. It is used to release moulds for stamped concrete from sticking to the concrete surface. **COLOR RELEASE** also acts as a curing compound and colouring agent to give a desired two tone effect.

TECHNICAL INFORMATION

Appearance:	Odourless coloured powder	Flash Point:	250°C
Boiling Point:	Approx 150°C	Flammability Limits:	N/A
Vapor Pressure:	N/A	Solubility in Water:	Insoluble
Specific Gravity:	N/A		

RECOMMENDED APPLICATION

COLOR RELEASE is packed in 10 kg pails. Shake well before use.

SHELF LIFE

Under normal conditions and kept dry, the shelf life of **COLOR RELEASE** is 3 years from production.

RATE OF APPLICATION

0.12- 0.2 kg/m²

APPLICATION

As soon as the application of COLOR HARDENER is completed and ready to stamp, final trowel the surface of the COLOR HARDENER and dry shake the **COLOR RELEASE** and apply the required tools to form the pattern surface.

WASH AND SEAL

2 - 3 days after stamping, wash excess releaser off with a garden hose or sweep dry. After 5 - 7 days, the surface shall be cleaned with a high pressure cleaner. All protruding edges shall be removed, rough surfaces ground-down and touch-up where necessary. After washing and when the surface is completely dry apply 1 - 2 coats CLEAR SEAL F1/50. Allow the first coat to dry before application of second coat.

PROTECTION

The finished floor shall be protected. Any heavy traffic shall be avoided for 28 days. (The main contractor shall take necessary steps to protect the finished floor from damage by other trades).

Rev: 07/07/20

DISCLAIMER: Tremco CPG Malaysia's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request. Any suggested practices or installation specifications for the composite system (as opposed to individual product performance specifications) included in this communication (or any other) from Tremco CPG Malaysia Sdn Bhd constitute potential options only and do not constitute nor replace professional advice in such regard. Tremco CPG Malaysia Sdn Bhd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.