

SINGLE COMPONENT SPRAY-DECK GROUT

POLYMER-MODIFIED CEMENTITIOUS COATING

DESCRIPTION

SINGLE-COMPONENT SPRAY-DECK GROUT is a pre-blended cementitious coating, and is an ideal horizontal cover-up for unsightly existing concrete. **SINGLE-COMPONENT SPRAY-DECK GROUT** is uniquely formulated with fine aggregate that transforms concrete or masonry substrates into a non-slip, textured surface.

PRIMARY APPLICATIONS

- Pool decks
- Shopping centres
- Walkways
- Residential and commercial entrances
- Patio decks
- Plazas
- Showroom floors

FEATURES

- One component, easy to mix and use
- Durable, wear-resistant
- May be integrally coloured
- Interior or exterior use
- Trowel, squeegee or spray apply

PACKAGING

SINGLE-COMPONENT SPRAY-DECK GROUT is available in a 25kg bag.

SHELF LIFE

1 year in original, unopened packaging.

COVERAGE

One bag of **SINGLE COMPONENT SPRAY-DECK GROUT** will cover 15.45 m² for a skim coat, 7.73 m² for a final coat. The average coverage can vary greatly depending upon the application process and the porosity of the surface. A test area is recommended to determine coverage rate and project requirements.

DIRECTIONS FOR USE

For complete detailed instructions, consult **SPRAY-DECK/TEXTURE-CRETE** Installation Instructions.

APPLICATION PROCESS

Surface Preparation: Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and other contaminants. Mechanically Abrade the surface to a profile of at least CSP 2, in accordance with ICRI Guideline 310.2-1997. Properly clean profiled area.

Mixing: Add 4.3 to 5.9 L of clean, potable, cold water to a clean 20 L pail plastic pail. Begin mixing while slowly adding one 25 kg bag of **SINGLE-COMPONENT SPRAY-DECK GROUT**. Continue mixing for 2 to 3 minutes.

Application: The grout can then be troweled, squeegeed, or sprayed on the surface at a thickness not to exceed 6.35 mm.

Seal: After at least 24 hours drying time, the surface must be scraped, broomed, and blown with a high velocity blower and then sealed with **EVERCLEAR M** or **Flowseal UV Clear**.

MAINTENANCE

Sweep surface as necessary. Wash surface with a mild soap/detergent and rinse with water.

Use **GREASE-AWAY** as needed.

FEATURES

- Protect surrounding areas and surfaces from overspray.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use

DISCLAIMER: Tremco CPG Malaysia's products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request. Any suggested practices or installation specifications for the composite system (as opposed to individual product performance specifications) included in this communication (or any other) from Tremco CPG Malaysia Sdn Bhd constitute potential options only and do not constitute nor replace professional advice in such regard. Tremco CPG Malaysia Sdn Bhd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.

Rev: 24/09/20