

# Tremco POWERply Standard Smooth

## For Protection of Liquid Applied and Sheet Waterproofing Membranes

### Product Description

Tremco POWERply Sheeting is a smooth surfaced, modified bitumen protection sheet which is strong, yet easy to handle. This sheet offers protection for the waterproofing membrane against abrasion, impact and puncture, during backfilling or application of a structural concrete wearing course.

### Basic Uses

Tremco POWERply Sheeting is recommended for use with TREMproof 60, TREMproof 250GC, Vulkem 201 and TREMproof 6100 for all vertical and horizontal applications.

Tremco POWERply Sheeting can also be used with sheet waterproofing systems during foundation backfilling and normal construction activities. Tremco POWERply Sheeting's lightweight structure permits easy handling and fitting around corners and projections. In addition, Tremco POWERply Sheeting is compatible for use with most liquid and sheet waterproofing systems.

### Limitations

- Do not use over horizontal surfaces where it will be directly exposed to vehicular traffic prior to the placement of a wearing course.
- Do not leave exposed for prolonged periods of water submersion.
- Do not apply over uncured membrane.
- Do not mechanically fasten to membrane.

### Packaging

Tremco POWERply Sheeting is supplied in 1 x 15m rolls. The both upper and lower faces of Tremco POWERply Sheeting are covered with an anti-adhesive finish layer.

### Installation

Tremco POWERply Sheeting should be applied by starting at the base of a vertical surface, then proceeding horizontally. Successive rows of Tremco POWERply Sheeting should be staggered to minimize vertical seams.

Sheets of Tremco POWERply Sheeting should be tightly butted or overlapped to cover the waterproofing membrane completely.

Tremco POWERply Sheeting can be easily trimmed to size with a sharp knife and can be creased and folded to provide continuous protection around corners.

### Warranty

Tremco warrants its Tremco POWERply Sheeting to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco POWERply Sheeting. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase of the quantity of Tremco POWERply Sheeting proved to be defective and Tremco shall not be liable for any loss or damage.

### Technical Data

TYPICAL PHYSICAL PROPERTIES	
<u>Properties</u>	<u>Typical Value</u>
Composition	APP Bitmen Modified
Thickness	80 mils (2mm)
Puncture Resistance	186N
Weight	37 kg
Dimensions	1 m x 15 m