



TREMguard FBM Bonding Adhesive

DESCRIPTION

Tremguard® FBM Bonding Adhesive is a water-based acrylic emulsion copolymer-based adhesive. useful for bonding TREMguard FMBM membranes to various substrates.

- Suitable for roofing and flashing membranes, including fleece-back membranes
- Compatible with polyiso and fiberboard, insulations, and fiberglass-faced gypsum panels
- Compatible with concrete, masonry, and wood flashing substrates

APPLICATIONS

Mating surfaces should be dry, clean, and free from oil, grease, and other contaminants. Stir the adhesive thoroughly before use, either manually or by means of powered mixing equipment. Apply adhesive evenly, avoiding puddles. Do not apply adhesive in lap areas, as this will prevent proper heat-welding. Using a standard solvent-resistant roller, apply the adhesive at the following coverage rates:

- Approximately 55.74 m² of bonded area per pail of 20kg. Apply only to the substrate surface. Install membrane immediately onto wet adhesive: do NOT allow adhesive to dry. Roll membrane onto the substrate surface and broom the membrane to ensure close contact between the membrane and the substrate surface.

PACKAGING

20kg/pail

WARRANTY

Tremco CPG warrants its Products to be free of defects in materials but makes no warranty as to appearance or colour. Since methods of application and on-site conditions are beyond our control and can affect performance. Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Membranes. Tremco CPG's sole obligation shall be, at its option, to replace, or refund the purchase of the quantity or Tremco Membranes proved to be defective and Tremco CPG shall not be liable for any loss or damage.

PROPERTY	VALUES
Base	water-based acrylic emulsion copolymer-based adhesive
Density	1.03 - 1.07 kg/ltr
Viscosity	14,000-18,000 cps
Coverage	2.95m ² /ltr
Total Solids	60-65%
Shelf Life	1 year, unopened
Application	Roller or brush