

TREMguard LLM Bonding Adhesive

DESCRIPTION

Tremguard® LLM Bonding Adhesive is a contacttype bonding adhesive specially designed for bonding TREMguard LLM membranes and flashings to various roofing substrates.

FEATURES

- Excellent coverage
- Fast-drying solvent system
- Multiple application options
- High initial tack

BENEFITS

- Up to 1.23m²/ltr of bonded membrane
- Quicker application
- Easy with roller or brush, spray application is also possible
- · Quick and easy application

BASIC USES

TREMguard LLM Bonding Adhesive is a general purpose, rubber-based bonding adhesive for attaching TPO based single-ply membranes to various substrates, including polyisocyanurate insulation and gypsum-based cover boards.

COLOUR

Transparent yellow liquid

PACKAGING

15kg / pail

APPLICATIONS

TREMguard LLM Bonding Adhesive should be applied on both sides of the materials to be bonded then let it dry until tacky to the touch before pressing them together. For effective bonding on absorbent surfaces and porous material normally two coats are required. Bond strength can be fully obtained after 24 hours.

WARRANTY

Tremco CPG warrants its Products to be free of defects in materials but makes no warranty as to appearance or colour. Since methods of application and on-site conditions are beyond our control and can affect performance. Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Membranes. Tremco CPG's sole obligation shall be, at its option, to replace, or refund the purchase of the quantity or Tremco Membranes proved to be defective and Tremco CPG shall not be liable for any loss or damage.

PROPERTY	VALUES
Base	Synthetic polymer
Solvent	Hydrocarbon blend
Flash point	4°C
Density	870kg/m³
Viscosity	2,400 - 2,800 cps
VOC	704g/ltr
Coverage	1.23m ² /ltr
Total Solids	19-21%
Shelf Life	1 year, unopened
Open time	Up to 60 minutes
Dry time	5-15minutes
Application	Roller, brush, or spray