



TREMPRIME® MULTI-SURFACE URETHANE PRIMER

Urethane Tie-In Primer

DESCRIPTION

TREMPRIME Multi-Surface Urethane Primer (MSUP) is a two-component, quick-drying, epoxy-based, water borne VOC-compliant primer primarily for use with Vulkem® urethane deck coating and liquid-applied waterproofing products. It may also be used with Vulkem and Tremco branded urethane sealants.

BASIC USES

Primer for porous surfaces, interlaminary and urethane coatings. Low-VOC (<60 g/L), two-part epoxy primer used to condition and prep porous surfaces and existing coatings for application of a new coating layer.

FEATURES & BENEFITS

- Reduces water and salt absorption
- Water-based, low odour
- Resistant to mild acids
- Can be used as a primer under epoxy or urethane coatings

PACKAGING

11.4- L (3 gallon) kits:

- Part A: 7.6 L (2 gallon) pail
- Part B: 3.8 L (1 gallon) can

COVERAGE

Concrete and porous substrates: 70-90 m² per 11.4 litre kit

Existing Coatings: 120-150 m² per 11.4 litre kit

Coverage will depend on the porosity and roughness of the substrate.

INSTALLATION

- All surfaces must be thoroughly clean, sound and free from grease, oils, waxes and all loose material.
- Apply generously with a clean brush or roller. Do not apply in excess where it will puddle or pond. At 25 °C, allow 1-2 hours for primer to become tacky before applying sealant, coating or membrane.
- Primer must dry completely before coating application as indicated by turning from milky-white to completely clear.
- Any questions regarding drying times, coverage rates and unique application techniques regarding should be directed to Tremco Technical Services or your local Tremco Sales Representative.

LIMITATIONS

- Protect from freezing.
- Do not apply at temperatures below 10°
- All surfaces must be sound, clean and free from contamination.
- A thorough wire brushing, grinding, sandblasting or solvent cleaning may be required to expose clean, sound, virgin surfaces.
- Do not apply over contaminated or damp surfaces.
- Do not thin.

WARRANTY

Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or colour. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

PROPERTY @ 23°C, 50% RH	DESCRIPTION
Mix Ratio (A:B by Volume)	2:1
VOC Content	< 70 g/L
Pot Life	4 - 6hrs
Storage Temperature Range	7°C minimum to 43°C maximum

To find your local office address and contact details, visit

www.tremcocpg-asiapacific.com

REV14/04/20