



# TREMproof® WP

## Elastic Waterproofing Exterior Coating

### DESCRIPTION

TREMproof WP is an elastic covering of creamy consistency, using styrene-acrylic copolymers in watery emulsion which, once dry, forms a flexible, waterproofing and durable film. TREMproof WP is a single component 'Ready to Use' formulation with quick drying properties at room temperature.

### BASIC USES

Waterproofing of roof on different types of substrate:

- Very porous tile terrace
- Fibrocement
- Zinc
- Aluminium
- Brick
- Concrete

Protection of partition walls against surface water infiltration

### FEATURES AND BENEFITS

- Waterproof to rain and splashes
- High elasticity
- Passable
- Easy application by traditional method
- Good penetration in cracks
- Resistant to cracking
- Water based, non-toxic or inflammable

### PACKAGING

Packed in 20 kg pails.

### DIRECTIONS FOR USE

**System Structure for vertical wall and roofing**

**applications:** 1 priming layer with diluted TREMproof WP (for very porous substrate) 3 layers of TREMproof WP.

**Consumption:** On roof and terraces: at least 2kg/m<sup>2</sup> in three or more layers.

On vertical walls: at least 1kg/m<sup>2</sup> applied in two coats.

**Mixing:** Mix TREMproof WP manually or with low- revolution mixer until it is completely homogenous.

**Application:** Apply with short-haired wool roller, brush or by airless spray. Using a short-haired roller or a brush, apply a layer of the product diluting 3 parts of TREMproof WP per 1 of water, observing that it penetrates well in all the cracks.

Once the priming is dry (approximately 12 hours after having been applied in normal temperature and relative humidity conditions), add successive layer of TREMproof WP until the film thickness desired is obtained. Before applying a layer, the previous one will have to be completely dry.

### CLEAN UP

Clean all the tools and application equipment with water immediately after use. Hardened and/or cured material can only be mechanically removed.

### SAFETY PRECAUTIONS

The Technical and Safety Data Sheets must be read and understood before use.

## WARRANTY

Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or colour. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase of the quantity or Tremco product proved to be defective and Tremco shall not be liable for any loss or damage.

PROPERTY	DESCRIPTION
Appearance	White or grey viscous liquid
Solid Content (%)	> 60 by weight
Adhesion Strength (N/mm <sup>2</sup> )	Approx. 1.2
Crack Bridging	No cracking up to 1mm
Shelf Life	12 months in original sealed container stored in a dry and cool place under cover out of direct sunlight.

*To find your local office address and contact details, visit*

[www.tremcocpg-asiapacific.com](http://www.tremcocpg-asiapacific.com)

REV13/04/20